



Product Data Sheet

PLUTUS M TBN 50

Product Description:

Plutus M TBN 50 marine lubricant is specially formulated engine oil for lubricating medium-speed trunk piston medium-speed diesel engines found on ships, coastal vessels, tugboats as well as land-based stationary power-generation equipment. Plutus M TBN 50 marine lubricant is suitable for use in engines burning residual fuels with a fuel sulfur content exceed 3.5% sulfur.

Plutus M TBN 50 marine lubricant contains a balanced additive composition used in conjunction with highly refined base oils to produce a product which imparts useful performance characteristics such as high load carrying capacity, good detergency and dispersancy properties, excellent rust and corrosion protection for all engine parts and strong alkalinity reserve to neutralize acids formed from the combustion of distillate fuels.

Plutus M TBN 50 marine lubricant is compatible with all medium-speed trunk-piston engine marine lubricants sold in the market and can be used for lubricating gear transmissions, turbo-chargers, oil lubricated stern tubes and other shipboard machinery.

Applications / Benefits:

- ▣ Good oxidation stability and water shedding properties.
- ▣ Good load bearing capacity.
- ▣ Rust and oxidation protection.
- ▣ Strong acid neutralizing properties.
- ▣ Compatible with other competitive lubricants.

Typical Characteristics:

Test Description	Method	450
SAE Viscosity Grade	SAE J 300	40
Specific Gravity @ 15 °C	ASTM D 4052	0.918
Flash Point, °C	ASTM D 92	245
Pour Point, °C	ASTM D 97	-9
Kinematic Viscosity, cSt @ 40°C	ASTM D 445	148
cSt @ 100°C	ASTM D 445	14.9
Viscosity Index	ASTM D 2270	100
TBN, mgKOH/g	ASTM D 2896	50
Color	ASTM D 1500	<5.5

Issued by HPURE Lubricant SG Tel: +65 6861 1157 www.hpure-lube.com

Furnishing the information contained does not constitute a representation by HPURE Lubricants that any product or process is free from patent infringement claims of any 3rd party nor does it constitute the granting of a license under any patent of HPURE Lubricants or any 3rd party. HPURE Lubricants assumes no liability for any infringement which might arise out of the use of the product. The information and suggestions for use & application presented herein represent the best information available to us and are believed to be reliable. They should not, however, be construed as controlling suggestions, and users are urged to conduct confirmatory test to determine final suitability for their specific end users. HPURE Lubricants warranty only that its products meet the specifications which it sets for them and specifically DISCLAIMS ALL OTHER WARRANTIES relating to the products and the application thereof, EXPRESS or IMPLIED

including and not limited to warranties of MERCHANTABILITY and FITNESS.