



Product Data Sheet

GLYCOL COOLANT

Product Description:

Glycol Coolant is a premium quality, single-phase, ethylene glycol based product. This product provides excellent heat rejecting aluminum protection for all automotive and light duty diesel applications. It also provides outstanding protection for heavy-duty diesel applications when combined with supplemental coolant additives. Glycol Coolant protects all commons cooling system metals including solder, copper, brass, steel, cast iron and aluminum. This formulation is compatible with all other major brands of coolant and will not affect automotive hoses and gaskets.

Glycol Coolant is recommended for automotive and trucks cooling systems. It contains an effective defoamer to prevent foaming in the cooling system for the life of coolant.

Glycol Coolant is recommended for use in all automobiles requiring ethylene glycol based coolant.

Applications / Benefits:

- ▢ Provides excellent heat rejecting properties.
- ▢ Protects most metal in cooling systems.
- ▢ Compatible with most commercial coolants.

Typical Characteristics:

Test Description	Method	
Specific Gravity @ 15 °C	ASTM D 4052	1.024
Freezing Point, °C	ASTM D 1177	-4
Boiling Point, °C	ASTM D 1120	102
Appearance	Visual	Pink/Green/Blue

Issued by HPURE Lubricant SG Tel: +65 6861 1157 www.hpure-lube.com

Furnishing the information contained does not constitute a representation by HPURE Lubricants that any product or process is free from patent infringement claims of any 3rd party nor does it constitute the granting of a license under any patent of HPURE Lubricants or any 3rd party. HPURE Lubricants assumes no liability for any infringement which might arise out of the use of the product. The information and suggestions for use & application presented herein represent the best information available to us and are believed to be reliable. They should not, however, be construed as controlling suggestions, and users are urged to conduct confirmatory test to determine final suitability for their specific end users. HPURE Lubricants warranty only that its products meet the specifications which it sets for them and specifically DISCLAIMS ALL OTHER WARRANTIES relating to the products and the application thereof, EXPRESS or IMPLIED

including and not limited to warranties of MERCHANTABILITY and FITNESS.