



PLUTUS HYDRAULIC OIL HVX

Product Description:

Plutus Hydraulic Oils HVX offer state of the art formulations that produce a line of universal anti-wear long life hydraulic oils having all the wear preventive characteristics required for the most severe of applications, including high pressure vane pumps. Plutus Hydraulic Oil HVX are produced from carefully selected high quality, highly refined hydro-treated base oil and the addition of a balanced additive system, including a shear stable viscosity index improver in these oils, thereby providing total year-round protection in a variety of application. It is formulated with ashless and zinc free additive package that make it suitable for pump containing steel-on-bronze lubrication surfaces and silver plate.

Plutus Hydraulic Oils HVX have excellent hydrolytic stability, providing protection to all hydraulic system components even in the presence of moisture. Additives used in some hydraulic oils break down under conditions of high temperature and moisture to form acids that can attack copper and its alloys such as brass and bronze.

Applications / Benefits:

- ▣ Outstanding cold temperature flow properties.
- ▣ Excellent anti-wear performance.
- ▣ Superior rust, anti-corrosion and oxidation stability.

Typical Characteristics:

Test Description	Method	32	46	68	100	150	220
ISO Viscosity Grade	-						
Specific Gravity @ 15 °C	ASTM D 4052	0.855	0.862	0.865	0.868	0.882	0.898
Flash Point, °C	ASTM D 92	200	212	210	230	232	235
Pour Point, °C	ASTM D 97	-39	-36	-36	-33	-30	-24
Kinematic Viscosity, cSt @ 40°C	ASTM D 445	31.6	44.5	66.1	99.6	145	225
cSt @ 100°C	ASTM D 445	6.21	7.8	10.6	14.8	19.1	25.6
Viscosity Index	ASTM D 2270	150	146	150	155	150	145
Color	ASTM D 1500	<0.5	<0.5	<0.5	<0.5	<1.5	<2.0

Issued by HPURE Lubricant SG Tel: +65 6861 1157 www.hpure-lube.com

Furnishing the information contained does not constitute a representation by HPURE Lubricants that any product or process is free from patent infringement claims of any 3rd party nor does it constitute the granting of a license under any patent of HPURE Lubricants or any 3rd party. HPURE Lubricants assumes no liability for any infringement which might arise out of the use of the product. The information and suggestions for use & application presented herein represent the best information available to us and are believed to be reliable. They should not, however, be construed as controlling suggestions, and users are urged to conduct confirmatory test to determine final suitability for their specific end users. HPURE Lubricants warranty only that its products meet the specifications which it sets for them and specifically DISCLAIMS ALL OTHER WARRANTIES relating to the products and the application thereof, EXPRESS or IMPLIED

including and not limited to warranties of MERCHANTABILITY and FITNESS.



Product Data Sheet

Specifications, Approvals & Recommendations:

- Denison HF-0, HF-1, and HF-2
- Jeffry No. 87,
- Ford M-61C13227 13,
- U.S Steel 127, 136
- Cincinnati Machine P- 68 (ISO 32)
- Cincinnati Machine P- 70 (ISO 46)
- Cincinnati Machine P- 69 (ISO 68)
- Vickers M-2590-S
- Vickers I-286-S
- Lee Norse 100-1
- General Motor LH-04-1
- General Motor LH-06-1
- General Motor LH-15-1
- B.F. Goodrich

Issued by HPURE Lubricant SG Tel: +65 6861 1157 www.hpure-lube.com

Furnishing the information contained does not constitute a representation by HPURE Lubricants that any product or process is free from patent infringement claims of any 3rd party nor does it constitute the granting of a license under any patent of HPURE Lubricants or any 3rd party. HPURE Lubricants assumes no liability for any infringement which might arise out of the use of the product. The information and suggestions for use & application presented herein represent the best information available to us and are believed to be reliable. They should not, however, be construed as controlling suggestions, and users are urged to conduct confirmatory test to determine final suitability for their specific end users. HPURE Lubricants warranty only that its products meet the specifications which it sets for them and specifically DISCLAIMS ALL OTHER WARRANTIES relating to the products and the application thereof, EXPRESS or IMPLIED

including and not limited to warranties of MERCHANTABILITY and FITNESS.