



PLUTUS WASHABLE TEXTILE OIL

Product Description:

Plutus Washable Textile Oil is a premium grade, specially designed product that can be used for lubricating knitting machines.

Containing highly refined base oil plus high performance, specially selected lubricity agent and emulsifier. Plutus Washable Textile Oil is essential light color and can give exceptional antiwear protection to the machine parts. The compounded emulsifier system effectively removes the oil stain from textile by emulsifying with water and thus makes the oil completely washable.

Plutus Washable Textile Oil is available in four viscosity grades for different lubrication requirement. It can be used widely for circular or tricot machine operations by spray, bath, or mist application.

Applications / Benefits:

- ▣ Special EP agent gives best anti-wear protection.
- ▣ Very light color and totally washable.
- ▣ Light viscosity ensures smooth operations.
- ▣ Maximizing knitting machine performance.

Typical Characteristics:

Test Description	Method	15	22	28	32	46
ISO Viscosity Grade	-	15	22	28	32	46
Specific Gravity @ 15 °C	ASTM D 4052	0.858	0.856	0.877	0.878	0.879
Flash Point, °C	ASTM D 92	184	196	218	218	220
Pour Point , °C	ASTM D 97	-12	-9	-9	-9	-9
Kinematic Viscosity, cSt @ 40°C	ASTM D 445	16.3	21.1	28.0	32.2	45.7
cSt @ 100°C	ASTM D 445	3.58	4.21	4.98	5.42	6.81
Viscosity Index	ASTM D 2270	100	102	102	102	103
Color	ASTM D 1500	0.5	0.5	0.5	0.5	<1.0

Issued by HPURE Lubricant SG Tel: +65 6861 1157 www.hpure-lube.com

Furnishing the information contained does not constitute a representation by HPURE Lubricants that any product or process is free from patent infringement claims of any 3rd party nor does it constitute the granting of a license under any patent of HPURE Lubricants or any 3rd party. HPURE Lubricants assumes no liability for any infringement which might arise out of the use of the product. The information and suggestions for use & application presented herein represent the best information available to us and are believed to be reliable. They should not, however, be construed as controlling suggestions, and users are urged to conduct confirmatory test to determine final suitability for their specific end users. HPURE Lubricants warranty only that its products meet the specifications which it sets for them and specifically DISCLAIMS ALL OTHER WARRANTIES relating to the products and the application thereof, EXPRESS or IMPLIED

including and not limited to warranties of MERCHANTABILITY and FITNESS.