



Product Data Sheet

MV ROCK DRILL OIL

Product Description:

MV Rock Drill Oil is blended with highly refined base oils and special additives which product a superior lubricant for air powered equipment. The naturally high viscosity index provides optimum lubrication for both low start-up temperatures and high operational temperatures. Extreme pressure additives prevent wear and withstand the high loads commonly encountered in rock drills, jack hammers and other pneumatic equipment.

MV Rock Drill Oil contains tackiness agents that permit them to tenaciously adhere to cylinder walls and other lubricated parts. They are also fortified with Molybdenum based friction and extreme pressure additives that protect rock drills against wear caused by load shocks.

MV Rock Drill Oil is specially developed for use in pneumatic equipment. They are recommended for rock drills, jack hammers, paving breakers, pile drivers, air tools and other pneumatic equipment.

Applications / Benefits:

- ▣ Excellent adhesion.
- ▣ Excellent dispersancy properties.
- ▣ Washout resistant.
- ▣ Protect against rust and corrosion.
- ▣ Contains organomolybdenum complex friction modifier

Typical Characteristics:

Test Description	Method	100	150	320	460
ISO Viscosity Grade	-	100	150	320	460
Specific Gravity @ 15 °C	ASTM D 4052	0.888	0.896	0.910	0.935
Flash Point, °C	ASTM D 92	244	252	252	260
Pour Point, °C	ASTM D 97	-9	-9	-6	-6
Kinematic Viscosity, cSt @ 40°C	ASTM D 445	102	146	318	485
cSt @ 100°C	ASTM D 445	11.6	14.7	24.4	32.0
Viscosity Index	ASTM D 2270	101	100	98	97
Color	ASTM D 1500	<2.5	<3.0	3.0	3.5
Timken OK Load, (lbs)		-	-	75	75
4 Ball EP, Weld Point (kg)		-	-	254	258
4 Ball EP, LWI (kg)		-	-	48	48

Issued by HPURE Lubricant SG Tel: +65 6861 1157 www.hpure-lube.com

Furnishing the information contained does not constitute a representation by HPURE Lubricants that any product or process is free from patent infringement claims of any 3rd party nor does it constitute the granting of a license under any patent of HPURE Lubricants or any 3rd party. HPURE Lubricants assumes no liability for any infringement which might arise out of the use of the product. The information and suggestions for use & application presented herein represent the best information available to us and are believed to be reliable. They should not, however, be construed as controlling suggestions, and users are urged to conduct confirmatory test to determine final suitability for their specific end users. HPURE Lubricants warranty only that its products meet the specifications which it sets for them and specifically DISCLAIMS ALL OTHER WARRANTIES relating to the products and the application thereof, EXPRESS or IMPLIED

including and not limited to warranties of MERCHANTABILITY and FITNESS.