



# Product Data Sheet

## SPINDLE OIL

### Product Description:

**Spindle Oil is a premium grade, severely refined oil based extra low viscosity product specially for lubricating high speed spindles in knitting machines.**

Adopting highly refined special grade base oil, Spindle oil is naturally in low odor and viscosity that are essential to be used to lubricate the lightly loaded spindles that rotated in very high speed and give good finish of the textile. Results in reduced operating temperature and much less machine or operation break down.

Spindle oil is available in viscosity grade 10 for optimized lubrication requirement. It can be used widely for most high speed, light duty spindles found in most types of textile machines.

### Applications / Benefits:

- ▣ Special grade base oil also gives good oil film protection.
- ▣ Very light color and low odor.
- ▣ Light viscosity ensures smooth operations.
- ▣ Maximizing knitting machine performance.

### Typical Characteristics:

Test Description	Method	2	3	5	10	15	22
ISO Viscosity Grade	-						
Specific Gravity @ 15 °C	ASTM D 4052	0.782	0.788	0.822	0.828	0.833	0.845
Flash Point, °C	ASTM D 92	80	120	145	175	190	202
Pour Point, °C	ASTM D 97	-18	-18	-24	-30	-21	-18
Kinematic Viscosity, cSt @ 40°C	ASTM D 445	2.26	3.50	5.02	10.2	14.89	22.4
cSt @ 100°C	ASTM D 445	-	-	-	2.86	3.52	4.38
Viscosity Index	ASTM D 2270	-	-	-	110	116	103
Color	ASTM D 1500	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5

Issued by HPURE Lubricant SG Tel: +65 6861 1157 [www.hpure-lube.com](http://www.hpure-lube.com)

Furnishing the information contained does not constitute a representation by HPURE Lubricants that any product or process is free from patent infringement claims of any 3<sup>rd</sup> party nor does it constitute the granting of a license under any patent of HPURE Lubricants or any 3<sup>rd</sup> party. HPURE Lubricants assumes no liability for any infringement which might arise out of the use of the product. The information and suggestions for use & application presented herein represent the best information available to us and are believed to be reliable. They should not, however, be construed as controlling suggestions, and users are urged to conduct confirmatory test to determine final suitability for their specific end users. HPURE Lubricants warranty only that its products meet the specifications which it sets for them and specifically DISCLAIMS ALL OTHER WARRANTIES relating to the products and the application thereof, EXPRESS or IMPLIED

including and not limited to warranties of MERCHANTABILITY and FITNESS.