



Product Data Sheet

AIR TOOL OIL

Product Description:

Air Tool Oil is a low zinc antiwear circulating oil meeting Denison HF-0 requirements. It is produced from highly refined lubricating base stocks and hydraulic oil additive packages. These products are designed for hydraulic systems with higher make up rates or those, which operate at moderate temperatures.

The additives found in Air Tool Oil enhance the anti-wear characteristics of the fluid. They also inhibit foam from forming in the oil and offer a moderate level of protection against rust and corrosion in the event of water contamination.

Air Tool Oil is suitable for applications used in equipment located in underground mines, industrial hygiene units and other hydraulic & pneumatic systems.

Applications / Benefits:

- ▣ Prevents wear.
- ▣ Protects against rust and corrosion.
- ▣ Resists foaming.
- ▣ Economical.

Typical Characteristics:

Test Description	Method	
ISO Viscosity Grade	-	100
Specific Gravity @ 15 °C	ASTM D 4052	0.888
Flash Point, °C	ASTM D 92	228
Pour Point, °C	ASTM D 97	-18
Kinematic Viscosity, cSt @ 40°C	ASTM D 445	98.2
cSt @ 100°C	ASTM D 445	11.2
Viscosity Index	ASTM D 2270	98
Color	ASTM D 1500	1.5

Issued by HPURE Lubricant SG Tel: +65 6861 1157 www.hpure-lube.com

Furnishing the information contained does not constitute a representation by HPURE Lubricants that any product or process is free from patent infringement claims of any 3rd party nor does it constitute the granting of a license under any patent of HPURE Lubricants or any 3rd party. HPURE Lubricants assumes no liability for any infringement which might arise out of the use of the product. The information and suggestions for use & application presented herein represent the best information available to us and are believed to be reliable. They should not, however, be construed as controlling suggestions, and users are urged to conduct confirmatory test to determine final suitability for their specific end users. HPURE Lubricants warranty only that its products meet the specifications which it sets for them and specifically DISCLAIMS ALL OTHER WARRANTIES relating to the products and the application thereof, EXPRESS or IMPLIED

including and not limited to warranties of MERCHANTABILITY and FITNESS.



Product Data Sheet

Specifications, Approvals & Recommendations:

- Denison HF-0
- Denison HF-1
- Denison HF-2
- Denison T-6H20C Hybrid Pump
- DIN 51524 Part I (HL) & II (HLP)
- DIN 51589 Part I at 6 min level (ISO 46)
- Vickers Vane Pump test (DIN 51589) Part II at 4.4 mg level
- Vickers M-2950-S
- Vickers 35VQ25A(H46)
- AFNOR NF E 48-603 (HL)
- Cincinnati Machine P-68
- Cincinnati Machine P-69
- Cincinnati Machine P-70
- US steel 127 & 136
- FZG A/8.3/90 Load test (DIN 51354) at 12th Stage level

Issued by HPURE Lubricant SG Tel: +65 6861 1157 www.hpure-lube.com

Furnishing the information contained does not constitute a representation by HPURE Lubricants that any product or process is free from patent infringement claims of any 3rd party nor does it constitute the granting of a license under any patent of HPURE Lubricants or any 3rd party. HPURE Lubricants assumes no liability for any infringement which might arise out of the use of the product. The information and suggestions for use & application presented herein represent the best information available to us and are believed to be reliable. They should not, however, be construed as controlling suggestions, and users are urged to conduct confirmatory test to determine final suitability for their specific end users. HPURE Lubricants warranty only that its products meet the specifications which it sets for them and specifically DISCLAIMS ALL OTHER WARRANTIES relating to the products and the application thereof, EXPRESS or IMPLIED

including and not limited to warranties of MERCHANTABILITY and FITNESS.