



Product Data Sheet

CHAIN AND BAR OIL

Product Description:

Chain and Bar Oil is a tacky lubricant designed for lubrication of the chain, bar and sprocket on all types of chainsaws and chain driven machinery. It is formulated with high quality paraffinic base oils and additives to optimize performance. Anti-wear agents reduce metal-to-metal contact wear between the drive sprocket, the bar guide and the moving chain. Highly effective tackiness agent to resist throw-off during operation. Tight control of viscosity allows for better calibration of oiling rates, and cleaning agents reduce the amount of pitch build-up on various parts.

Chain and Bar Oil is applicable for all brands of chain saws - including today's high performance and industrial saws, as well as older models. ISO 68(SAE 20) is recommended for winter conditions when temperatures are consistently below 0°C. ISO 100(SAE 30) is used for cool weather conditions of 15-0°C to help assure a proper flow from either hand operated or automatic chain oilers. ISO 150(SAE 40) and ISO 220(SAE 50) are a good choice for use in mild climates and provides excellent wear protection under hot weather operating conditions.

Applications / Benefits:

- Tacky additives reduce throw or fling off
- Special additive system reduces wear of components
- Flushes chips, dust and sap from the working surfaces
- Blades remain sharper for longer periods
- Provides corrosion protection to chain and bar

Typical Characteristics:

Test Description	Method	20	30	40	50
SAE Viscosity Grade	SAE J 300	20	30	40	50
ISO Viscosity Grade	-	68	100	150	220
Specific Gravity @ 15 °C	ASTM D 4052	0.878	0.880	0.885	0.889
Flash Point, °C	ASTM D 92	230	240	250	252
Pour Point, °C	ASTM D 97	-12	-9	-9	-9
Kinematic Viscosity, cSt @ 40°C	ASTM D 445	68	100	150	220
cSt @ 100°C	ASTM D 445	8.65	11.3	14.8	19.3
Viscosity Index	ASTM D 2270	98	98	98	99
Color	ASTM D 1500	<1.5	<2.0	<2.5	2.5

Issued by HPURE Lubricant SG Tel: +65 6861 1157 www.hpure-lube.com

Furnishing the information contained does not constitute a representation by HPURE Lubricants that any product or process is free from patent infringement claims of any 3rd party nor does it constitute the granting of a license under any patent of HPURE Lubricants or any 3rd party. HPURE Lubricants assumes no liability for any infringement which might arise out of the use of the product. The information and suggestions for use & application presented herein represent the best information available to us and are believed to be reliable. They should not, however, be construed as controlling suggestions, and users are urged to conduct confirmatory test to determine final suitability for their specific end users. HPURE Lubricants warranty only that its products meet the specifications which it sets for them and specifically DISCLAIMS ALL OTHER WARRANTIES relating to the products and the application thereof, EXPRESS or IMPLIED

including and not limited to warranties of MERCHANTABILITY and FITNESS.