

# HPURE FTR SPRINT 4T

## Product Description

Semi-synthetic motorcycle oil is a multigrade lubricant designed for four-stroke motorcycle engines. It contains a balanced blend of a specially selected synthetic base, high viscosity index base stocks and a special proprietary additive package. This oil is engineered to provide unsurpassed wear protection, engine cleanliness and oxidation resistance, as well as consistent viscosity.

This oil is a powerful detergent type of motor oil. It can be used in most 4T engines including Yamaha, Honda, Kawasaki, Suzuki, and Kubota.

## Applications / Benefits

- Υ Reduces engine wear and extends engine life
- Υ Protects engine under severe operating conditions
- Υ Retards harmful deposit formation on vital engine parts
- Υ Protects against rust and corrosion

## Typical Characteristics

Test Description	Method	Unit	10W30	10W40	10W50	15W50
SAE Viscosity Grade	SAE J 300	-	10W30	10W40	10W50	15W50
Density @ 15 °C	ASTM D 4052	kg/L	0.861	0.861	0.862	0.871
Flash Point	ASTM D 92	°C	218	218	220	228
Pour Point	ASTM D 97	°C	-33	-33	-33	-27
Kinematic Viscosity @ 40°C	ASTM D 445	cSt	75.38	97.33	133.5	151.9
Kinematic Viscosity @ 100°C	ASTM D 445	cSt	11.36	14.77	19.1	19.56
Viscosity Index	ASTM D 2270	-	143	158	162	148
TBN	ASTM D 2896	mgKOH/g	7.0	7.0	7.0	7.0

## Typical Characteristics

Test Description	Method	Unit	
SAE Viscosity Grade	SAE J 300	-	<b>20W50</b>
Flash Point	ASTM D 92	°C	0.878
Pour Point	ASTM D 97	°C	248
Kinematic Viscosity @ 40°C	ASTM D 445	cSt	-21
Kinematic Viscosity @ 100°C	ASTM D 445	cSt	162.2
Viscosity Index	ASTM D 2270	-	19.36
TBN	ASTM D 2896	mgKOH/g	137
CCS	ASTM D 5293	cP	7.0

## Specifications, Approvals & Recommendations

∩ API	SP
∩ JASO	MA2

Reference No.  
61209545G23SPMA2REV0

Last revised date:  
19/9/2023