

HPURE NITRON G15 PLUS

Product Description

Passenger car motor oil (PCMO) delivers the latest development of lubricating oil technology to maximize protection for the newest gasoline fueled engines. It meets the highest performance level of API SP and exceeds the most demanding requirements of modern engine's emission control and oil consumption standards. In today's energy conscious era, this oil is also formulated to improve fuel efficiency for consumers.

Applications / Benefits

- Υ Exceeds the highest U.S Lubricating oils standards for gasoline and LPG/CNG engines.
- Υ Silky smooth operation for all high performance engines.
- Υ Increases emission system durability and improves fuel efficiency.
- Υ Improves piston cleanliness and increases engine sludge protection.

Typical Characteristics

Test Description	Method	Unit	5W40	10W40
SAE Viscosity Grade	SAE J 300	-	5W40	10W40
Density @ 15 °C	ASTM D 4052	kg/L	0.8590	0.8580
Flash Point	ASTM D 92	°C	216	218
Pour Point	ASTM D 97	°C	-39	-33
Kinematic Viscosity @ 40°C	ASTM D 445	cSt	96.5	97.9
Kinematic Viscosity @ 100°C	ASTM D 445	cSt	15.3	14.8
Viscosity Index	ASTM D 2270	-	169	159
TBN	ASTM D 2896	mgKOH/g	7	7
CCS	ASTM D 5293	cP	5019	4833

Specifications, Approvals & Recommendations

- Υ API SP