

URE Product Data Sheet

OPTIMA D8

Product Description:

Today's technology trend of diesel engine is towards more environment conscious products with less gas emission and longer overhaul period. Coming along with these development, new devices like the Exhaust Gas Recirculation(EGR) rely much more on the performance of the engine oil being used. Optima D8 diesel engine oil, the newest product of our series high performance heavy diesel engine oils, is well positioned to address those needs.

Blended from hydrocracked base stocks and a state-of-art additive package, Optima D8 diesel engine oil is truly a universal lubricant required for EPA 2007 compliant diesel engines equipped with after treatment devices such as diesel oxidation catalysts and particulate filters. It also meets the latest European ACEA standards and American API performance. This means Optima D800 diesel engine oil is simply the top player for both the modern North American engines and the top-tier European engines.

Applications / Benefits:

- Provide unsurpassed control of soot.
- Protection of highly stressed piston rings and cylinder liners.
- Exceptional protection of valve train system used in modern diesel system.
- Satisfying most diesel engine OEM oil demand.
- Exceeds the highest API gasoline engine performance as well.
- 1 Particular suitable for the latest diesel engine meeting EURO IV, EURO V and EURO VI emission requirements.

Typical Characteristics:

Test Description	Method		
SAE Viscosity Grade	SAE J 300	10W30	15W40
Specific Gravity @ 15 °C	ASTM D 4052	0.864	0.882
Flash Point, °C	ASTM D 92	214	220
Pour Point, °C	ASTM D 97	-30	-27
Kinematic Viscosity, cSt @ 40°C	ASTM D 445	78.5	116.6
cSt @ 100°C	ASTM D 445	11.6	14.9
Viscosity Index	ASTM D 2270	140	132
TBN, mgKOH/g	ASTM D 2896	9.5	9.5
Color	ASTM D 1500	<3.0	<3.0

Furnishing the information contained does not constitute a representation by HPURE Lubricants that any product or process is free from patent infringement claims of any 3'4 party nor does it constitute the granting of a license under any patent of HPURE Lubricants or any 3'4 party. HPURE Lubricants assumes no liability for any infringement which might arise out of the use of the product. The information and suggestions for use & application presented herein represent the best information available to us and are believed to be reliable. They should not, however, be construed as controlling suggestions, and users are urged to conduct confirmatory test to determine final suitability for their specific end users. HPURE Lubricants warranty only that its products meet the specifications which it sets for them and specifically DISCLAIMS ALL OTHER WARRANTIES relating to the products and the application thereof, EXPRESS or IMPLIED



Specifications, Approvals & Recommendations:

- API CJ-4/CI-4 Plus/CI-4/CH-4/SN/SM
- API CJ-4/CF/SL
- MB-Approval 228.31
- ACEA E7-08
- ACEA E9-08
- Cummins CES 20081 & CES 20077, 76, 71
- Volvo VDS-4, VDS-3
- RVI RDL-3
- Detroit Diesel DDC 93K218, 93K215
- Caterpillar ECF-3
- Caterpillar ECF-2
- Caterpillar ECF-1A
- MAN M3275
- Mack EO-O Premium Plus, Mack EO-M Plus

Furnishing the information contained does not constitute a representation by HPURE Lubricants that any product or process is free from patent infringement claims of any 3'4 party nor does it constitute the granting of a license under any patent of HPURE Lubricants or any 3'4 party. HPURE Lubricants assumes no liability for any infringement which might arise out of the use of the product. The information and suggestions for use & application presented herein represent the best information available to us and are believed to be reliable. They should not, however, be construed as controlling suggestions, and users are urged to conduct confirmatory test to determine final suitability for their specific end users. HPURE Lubricants warranty only that its products meet the specifications which it sets for them and specifically DISCLAIMS ALL OTHER WARRANTIES relating to the products and the application thereof, EXPRESS or IMPLIED