



Product Data Sheet

AUTOTRONIC ATF

Product Description:

Autotronic ATF are a series new generation petroleum based product for automatic and powershift transmissions. The highest level product of ATF are suitable for use both GM Dexron III and Ford Mercon . In addition, it also meets Allison C-4 fluid and is qualified as a PSF specification.

Autotronic ATF are recommended for mobile equipment used by utility companies, which require electrical insulating properties for hydraulic oils. Autotronic ATF provide superior wear protection for all passenger car and light trucks requiring the use of TASA, Dexron II D, Dexron II E or Dexron III G/H ATFs. As well as the products are recommended for use by Volkswagen, Subaru, Isuzu, Fiat, Audi, Renault, Porsche and Mercedes Benz.

Applications / Benefits:

- ▣ Provides excellent friction, oxidation and thermal stability.
- ▣ Outstanding anti-wear properties.
- ▣ Improves hydrolytic stability.
- ▣ Better cold temperature flow properties than SAE 10W motor oil.

Typical Characteristics:

Test Description	Method	DEXRON		DEXRON
		TASA	II D	III G/H
Specific Gravity @ 15 °C	ASTM D 4052	0.856	0.854	0.853
Flash Point, °C	ASTM D 92	200	198	194
Pour Point , °C	ASTM D 97	-33	-36	-45
Kinematic Viscosity, cSt @ 40°C	ASTM D 445	40.2	37.0	35.7
cSt @ 100°C	ASTM D 445	7.7	7.4	7.3
Viscosity Index	ASTM D 2270	166	170	175
Appearance	Visual	Red	Red	Red

Issued by HPURE Lubricant SG Tel: +65 6861 1157 www.hpure-lube.com

Furnishing the information contained does not constitute a representation by HPURE Lubricants that any product or process is free from patent infringement claims of any 3rd party nor does it constitute the granting of a license under any patent of HPURE Lubricants or any 3rd party. HPURE Lubricants assumes no liability for any infringement which might arise out of the use of the product. The information and suggestions for use & application presented herein represent the best information available to us and are believed to be reliable. They should not, however, be construed as controlling suggestions, and users are urged to conduct confirmatory test to determine final suitability for their specific end users. HPURE Lubricants warranty only that its products meet the specifications which it sets for them and specifically DISCLAIMS ALL OTHER WARRANTIES relating to the products and the application thereof, EXPRESS or IMPLIED

including and not limited to warranties of MERCHANTABILITY and FITNESS.



Product Data Sheet

Specifications, Recommendations & Suitable For Use :

	TASA	DEXRON II D	DEXRON III G/H
• DEXRON III H	-	-	√
• DEXRON III G	-	-	√
• DEXRON II E	-	√	√
• DEXRON II D	-	√	√
• Ford M	-	-	√
• ALLISON C-4	-	-	√
• PSF	-	√	√
• TASA	√	√	√
• Cat TO-2	-	-	√
• Ford ESP-M2C166-H	-	-	√
• Ford ESP-M2C138-CJ	-	-	√
• MB 236.2	-	-	√

Issued by HPURE Lubricant SG Tel: +65 6861 1157 www.hpure-lube.com

Furnishing the information contained does not constitute a representation by HPURE Lubricants that any product or process is free from patent infringement claims of any 3rd party nor does it constitute the granting of a license under any patent of HPURE Lubricants or any 3rd party. HPURE Lubricants assumes no liability for any infringement which might arise out of the use of the product. The information and suggestions for use & application presented herein represent the best information available to us and are believed to be reliable. They should not, however, be construed as controlling suggestions, and users are urged to conduct confirmatory test to determine final suitability for their specific end users. HPURE Lubricants warranty only that its products meet the specifications which it sets for them and specifically DISCLAIMS ALL OTHER WARRANTIES relating to the products and the application thereof, EXPRESS or IMPLIED

including and not limited to warranties of MERCHANTABILITY and FITNESS.