



Product Data Sheet

AUTOTRONIC ATF 5

Product Description:

Autotronic ATF 5 is a premium synthetic automatic transmission fluid. It is formulated with selected high viscosity index synthetic base stocks and latest additive technology available allowing very high performance needed for the demanding requirements of passenger cars automatic gearboxes. Autotronic ATF 5 can be used in a broad range of automatic transmission standards and provides excellent service in a wide variety of North American, European, and Asian vehicles. It's particularly suitable for 4 and 5 speeds automatic transmissions.

Autotronic ATF 5 is recommended for use in all GM vehicles DII, DIII(G), DIII(H). It exceeds the published JASO 1A, Ford M and Allison C-4 fluid specifications and suitable for use in automatic transmission recommending Toyota Type T-IV.

Applications / Benefits:

- ▣ Provides excellent oxidation and thermal stability for longer life.
- ▣ Superior wear protection to protect critical transmission components.
- ▣ Excellent viscosity stability(high VI), application in a wide variety of Auto Transmission.
- ▣ Excellent friction and anti-shudder performances, improve driver's comfort with smooth and efficient shifting.
- ▣ Much enhanced fluidity at very low temperature service.
- ▣ Excellent rust and corrosion protection.

Typical Characteristics:

Test Description	Method	
Specific Gravity @ 15 °C	ASTM D 4052	0.853
Flash Point, °C	ASTM D 92	198
Pour Point, °C	ASTM D 97	-45
Kinematic Viscosity, cSt @ 40°C	ASTM D 445	38.1
cSt @ 100°C	ASTM D 445	7.24
Viscosity Index	ASTM D 2270	157
Color	ASTM D 1500	Red

Specifications, Approvals & Recommendations:

ATF T-IV

SFU

Issued by HPURE Lubricant SG Tel: +65 6861 1157 www.hpure-lube.com

Furnishing the information contained does not constitute a representation by HPURE Lubricants that any product or process is free from patent infringement claims of any 3rd party nor does it constitute the granting of a license under any patent of HPURE Lubricants or any 3rd party. HPURE Lubricants assumes no liability for any infringement which might arise out of the use of the product. The information and suggestions for use & application presented herein represent the best information available to us and are believed to be reliable. They should not, however, be construed as controlling suggestions, and users are urged to conduct confirmatory test to determine final suitability for their specific end users. HPURE Lubricants warranty only that its products meet the specifications which it sets for them and specifically DISCLAIMS ALL OTHER WARRANTIES relating to the products and the application thereof, EXPRESS or IMPLIED

including and not limited to warranties of MERCHANTABILITY and FITNESS.