

URE Product Data Sheet

POWER STEERING FLUID

Product Description:

Power Steering Fluid is manufactured from highly refined base oils and chemical additives to meet a lot of passenger car or commercial vehicle performance demands, such as for Ford, General Motors, Mercedes Benz, Chrysler, Honda, Toyota, Mitsubishi, Nissan, Hyundai, Kia and so on. Power Steering Fluid also meets Allison C-3 fluid and is qualified as a PSF, TASA specification.

Power Steering Fluid is essential ashless thus lubricates and transmits the pressure needed for power-assisted steering with minimum sludge and deposit created. It's compatible to most hose and seal used in the power steering system. Power Steering Fluid is recommended for power steering system, mobile equipment used by utility companies, hydraulic systems which require electrical insulating properties for their lubrication.

Applications / Benefits:

- Provides excellent friction, oxidation and thermal stability.
- Outstanding anti-wear properties.
- Improves hydrolytic stability.
- Better cold temperature flow properties than SAE 10W motor oil.

Typical Characteristics:

Test Description	Method	
Specific Gravity @ 15 °C	ASTM D 4052	0.858
Flash Point, °C	ASTM D 92	202
Pour Point, °C	ASTM D 97	-39
Kinematic Viscosity, cSt @ 40°C	ASTM D 445	36.9
cSt @ 100°C	ASTM D 445	6.81
Viscosity Index	ASTM D 2270	145
Appearance	Visual	Red / Neutral

Specifications, Approvals & Recommendations:

 Chrysler MS-1872 Chrtsler MS-5931, P/N 04883077 Ford M2C195-A GM P/N 89021184 GM 9985010, P/N 1052884 Hyundai PSF-3 Kia PSF-3 	SFU SFU SFU SFU SFU SFU
MB 236.3, P/N 000 989 88 03Mitsubishi PS Fluid	SFU
Mitsubishi Diamond SP III	SFU
Nissan PSF-II	SFU
 Saab P/N (45) 30 09 800 	SFU
 Subaru P/N K0209A0080 	SFU

Issued by HPURE Lubricant SG Tel: +65 6861 1157 www.hpure-lube.com

Furnishing the information contained does not constitute a representation by HPURE Lubricants that any product or process is free from patent infringement claims of any 3'4 party nor does it constitute the granting of a license under any patent of HPURE Lubricants or any 3'4 party. HPURE Lubricants assumes no liability for any infringement which might arise out of the use of the product. The information and suggestions for use & application presented herein represent the best information available to us and are believed to be reliable. They should not, however, be construed as controlling suggestions, and users are urged to conduct confirmatory test to determine final suitability for their specific end users. HPURE Lubricants warranty only that its products meet the specifications which it sets for them and specifically DISCLAIMS ALL OTHER WARRANTIES relating to the products and the application thereof, EXPRESS or IMPLIED