



Product Data Sheet

FTR 2T

Product Description:

FTR 2T is a premium quality lubricant formulated to meet API TB requirement by providing engine cleanliness, reducing spark plug fouling, port blocking and scuff formation. It provides rust protection and enhances pre-ignition for optimum performance power. It is suitable for most popular types of air-cooled motorcycle engines particularly for the high performance motorcycle with oil injection systems.

FTR 2T is suitable to use with pre-mixed petrol-oil or separate oil injection systems. Therefore, it can be introduced directly into the petrol tank with no prior mixing required. The petrol to oil ratio should be in accordance with the engine manufacturer's recommendations.

Applications / Benefits:

- ▣ Good engine cleanliness plus high resistance to deposit formation.
- ▣ Cleans and completely combustible .
- ▣ Good engine protection.
- ▣ Maximizing engine performance.

Typical Characteristics:

Test Description	Method	
Specific Gravity @ 15 °C	ASTM D 4052	0.881
Flash Point, °C	ASTM D 92	222
Pour Point , °C	ASTM D 97	-9
Kinematic Viscosity, cSt @ 40°C	ASTM D 445	52.76
cSt @ 100°C	ASTM D 445	7.852
Viscosity Index	ASTM D 2270	115
Color	ASTM D 1500	Green
Odor	-	Strawberry

Specifications, Approvals & Recommendations:

- API TB

Issued by HPURE Lubricant SG Tel: +65 6861 1157 www.hpure-lube.com

Furnishing the information contained does not constitute a representation by HPURE Lubricants that any product or process is free from patent infringement claims of any 3rd party nor does it constitute the granting of a license under any patent of HPURE Lubricants or any 3rd party. HPURE Lubricants assumes no liability for any infringement which might arise out of the use of the product. The information and suggestions for use & application presented herein represent the best information available to us and are believed to be reliable. They should not, however, be construed as controlling suggestions, and users are urged to conduct confirmatory test to determine final suitability for their specific end users. HPURE Lubricants warranty only that its products meet the specifications which it sets for them and specifically DISCLAIMS ALL OTHER WARRANTIES relating to the products and the application thereof, EXPRESS or IMPLIED

including and not limited to warranties of MERCHANTABILITY and FITNESS.