



# Product Data Sheet

## FTR SUPER 4T API SG

### Product Description:

FTR Super 4T motorcycle oil is a multigrade lubricant designed for four-stroke motorcycle engines. It contains a balanced blend of select high performance, high viscosity index base stocks and a special proprietary additive package. FTR Super 4T motorcycle oil is engineered to provide unsurpassed wear protection, engine cleanliness and oxidation resistance, as well as consistent viscosity.

FTR Super 4T is a powerful detergent type of motor oil. It can be used in most 4T engines including Yamaha, Honda, Kawasaki, Suzuki, and Kubota.

### Applications / Benefits:

- ▣ Reduces engine wear and extends engine life.
- ▣ Protects engine under severe operating conditions.
- ▣ Retards harmful deposit formation on vital engine parts.
- ▣ Protects against rust and corrosion.

### Typical Characteristics:

Test Description	Method	10W-30	10W-40	15W-40	20W-40	15W-50	20W-50
SAE Viscosity Grade	SAE J 300						
Specific Gravity @ 15 °C	ASTM D 4052	0.878	0.882	0.886	0.888	0.885	0.893
Flash Point, °C	ASTM D 92	212	215	220	232	224	235
Pour Point, °C	ASTM D 97	-30	-27	-24	-18	-24	-18
Kinematic Viscosity, cSt @ 40°C	ASTM D 445	78.1	102	109	138	145	175
cSt @ 100°C	ASTM D 445	11.8	14.9	15.0	15.4	18.9	19.5
Viscosity Index	ASTM D 2270	145	152	143	115	148	128
TBN, mgKOH/g	ASTM D 2896	5.4	5.4	5.4	5.4	5.4	5.4
Color	ASTM D 1500	2.5	2.5	2.5	2.5	2.5	2.5

### Specifications, Approvals & Recommendations:

- API SG
- JASO MA

Issued by HPURE Lubricant SG Tel: +65 6861 1157 [www.hpure-lube.com](http://www.hpure-lube.com)

Furnishing the information contained does not constitute a representation by HPURE Lubricants that any product or process is free from patent infringement claims of any 3<sup>rd</sup> party nor does it constitute the granting of a license under any patent of HPURE Lubricants or any 3<sup>rd</sup> party. HPURE Lubricants assumes no liability for any infringement which might arise out of the use of the product. The information and suggestions for use & application presented herein represent the best information available to us and are believed to be reliable. They should not, however, be construed as controlling suggestions, and users are urged to conduct confirmatory test to determine final suitability for their specific end users. HPURE Lubricants warranty only that its products meet the specifications which it sets for them and specifically DISCLAIMS ALL OTHER WARRANTIES relating to the products and the application thereof, EXPRESS or IMPLIED

including and not limited to warranties of MERCHANTABILITY and FITNESS.