



Product Data Sheet

PLUTUS M TBN 8

Product Description:

Plutus M TBN 8 lubricant is specially formulated marine system oil for lubricating medium-speed and high-speed auxiliary shipboard machineries on board ships. Plutus M TBN 8 is specifically suitable for lubricating gear transmissions, turbo chargers as well as oil lubricated stern tubes.

Plutus M TBN 8 lubricant contains balanced additive composition used in conjunction with highly refined base oils to produce a product which imparts useful performance characteristics such as high load carrying capacity, good detergency and dispersancy properties, excellent rust and corrosion protection and outstanding anti-oxidation properties for all engine parts and ship borne machineries.

Plutus M TBN 8 is compatible with all major auxiliary engine marine lubricants and can be used for all stationary shipboard auxiliary equipment.

Applications / Benefits:

- High load carrying capacity.
- Rust and oxidation protection.
- Outstanding anti-oxidation properties.
- Compatible with other competitive lubricants.

Typical Characteristics:

Test Description	Method	308	408	508
SAE Viscosity Grade	SAE J 300	30	40	50
Specific Gravity @ 15 °C	ASTM D 4052	0.894	0.898	0.901
Flash Point, °C	ASTM D 92	230	240	250
Pour Point, °C	ASTM D 97	-9	-9	-9
Kinematic Viscosity, cSt @ 40°C	ASTM D 445	102.6	145.5	202.9
cSt @ 100°C	ASTM D 445	11.46	14.42	17.94
Viscosity Index	ASTM D 2270	98	97	96
TBN, mgKOH/g	ASTM D 2896	8.0	8.0	8.0
Color	ASTM D 1500	<3.0	<3.0	<3.0

Issued by HPURE Lubricant SG Tel: +65 6861 1157 www.hpure-lube.com

Furnishing the information contained does not constitute a representation by HPURE Lubricants that any product or process is free from patent infringement claims of any 3rd party nor does it constitute the granting of a license under any patent of HPURE Lubricants or any 3rd party. HPURE Lubricants assumes no liability for any infringement which might arise out of the use of the product. The information and suggestions for use & application presented herein represent the best information available to us and are believed to be reliable. They should not, however, be construed as controlling suggestions, and users are urged to conduct confirmatory test to determine final suitability for their specific end users. HPURE Lubricants warranty only that its products meet the specifications which it sets for them and specifically DISCLAIMS ALL OTHER WARRANTIES relating to the products and the application thereof, EXPRESS or IMPLIED

including and not limited to warranties of MERCHANTABILITY and FITNESS.